

AIR130-3100

大惯量	High inertia
高速度	High speed
高稳定性	High stability


- 大负载，大惯量，高刚性，实现大尺寸、大偏心的负载的高速搬运。
  Large payload, high inertia and high rigidity ensure high-speed handling operation with large-sized, large-eccentric loads.
- 采用高速、高过载电机，能量密度高，力矩波动小，运行更平稳。
  With higher energy density and smaller torque fluctuations, smoother operation can be achieved by using high-speed and high-overload motors.
- 内置气管和 IO 线束，有效减少外挂线束对周边设备的干扰。
  Built-in air tubes and IO wiring harness, effectively reduces the interference of external wiring harness to peripheral equipment.


型号 Type		AIR130-3100
轴数 Axes		6
负载 Payload		130kg
机器人本体 Manipulator	重量 Weight	1245kg
	最大运动范围 Reach	3104mm
定位精度 Positioning accuracy	位置重复定位精度 Position repeatability	±0.06mm
IP 等级 Ingress Protection		IP54（腕部 : IP65） IP54（Wrist : IP65）
安装方式 Mounting		地装 Floor
运动范围 Working range	轴 1 Axis 1 rotation	-180°/+180°
	轴 2 Axis 2 arm	-60°/+85°
	轴 3 Axis 3 arm	-110°/+170°
	轴 4 Axis 4 wrist	-200°/+200°
	轴 5 Axis 5 bend	-135°/+135°
	轴 6 Axis 6 turn	-360°/+360°
运动速度 Rotation rate	轴 1 Axis 1 rotation	120°/s
	轴 2 Axis 2 arm	114°/s
	轴 3 Axis 3 arm	125°/s
	轴 4 Axis 4 wrist	225°/s
	轴 5 Axis 5 bend	210°/s
	轴 6 Axis 6 turn	300°/s
适用控制柜 Controllers		ARC5-280
安装条件 Mounting conditions	环境温度：0~45℃ Ambient temperature: 0~45℃ 湿度：恒温下 95% 以内，无凝露。 Humidity: not more than 95% at constant temperature without condensation. 允许高度：操作机正常工作环境的海拔高度不应超过 1000 米（在 1000 米 -4000 米高度范围内，操作机应降额使用）。 Allowable altitude: not more than 1000m above sea level. 不应有腐蚀性、可燃性、易爆性气体。 No corrosive, flammable or explosive gases.	




AIR130-3100

外形尺寸及运动范围 Outline dimension and Working range









大臂孔位图
Lower arm


小臂孔位图
Upper arm





肘部孔位图
Elbow arm

法兰图 Flange drawing



底座安装图 Base installation drawing

